

# Water Dispenser Catalogue (Filtration / Direct Pipe In Type)



**Model: GWS-175SS**

**Floor Standing (Hot, Warm & Cold Water)**

Product Specification:

Voltage: 220V-240V / AC 50Hz

Heating Power: 800W

Cooling Power: 205W

Hot Water Supply: 8 L / Hour

Cold Water Supply: 8 L / Hour

Power Consumption: 1.0KW.H/24H

Refrigeration Pour: R134a / 200G

Working Ambient: 10 -38°C

100% Stainless Steel | Made in Taiwan ROC

Dimension : 490mm (width) x 450mm (depth) x 1330mm (height)



# Water Dispenser Catalogue (Filtration / Direct Pipe In Type)



**Model: GWS-291C**

**Floor Standing Water Cooler  
(Hot & Cold Water)**

Product Specification:

Voltage: 220V-240V / AC 50Hz

Cooling Power: 205W

Heating Power: 800W

Stainless steel water storage tank

Cool Water Supply: 8 Liter / Hour

Power Consumption: 1.0KW.H/24H

Refrigeration Pour: R134a / 200G

Working Ambient: 10 -38°C

100% Stainless Steel

Dimension : 463mm (width) x 315mm (depth) x 1140mm (height)



# Water Dispenser Catalogue (Filtration / Direct Pipe In Type)



**Model: GWS-293C**

**Floor Standing Water Cooler  
(Cold Water)**

Product Specification:

Voltage: 220V-240V / AC 50Hz

Power: Cooling 205W

Stainless steel water storage tank

Water Supply: Cold 8 Liters / Hour

Power Consumption: 1.0KW / H

Refrigeration Pour: R134a / 200G

Working Ambient: 10 -38°C

100% Stainless Steel

Dimension : 463mm (width) x 315mm (depth) x 1140mm (height)



# Water Dispenser Catalogue (Filtration / Direct Pipe In Type)



**Model: GWS-880**

**Floor Standing  
(Normal & Cold Water)**

Product Specification:

Cold Tank Capacity: 10L

Normal Tank Capacity: 18L

Dimension (mm): H1300 x W430 x D550



# Water Dispenser Catalogue (Filtration / Direct Pipe In Type)



**Model: GWS-C100**

**Floor Standing  
(Hot & Cold Water)**

Product Specification:

Volt./ Hz: 220-240V/50-60Hz

Power Consumption:

Cooling System: 100W

Heating System: 450W

Compressor: 1/15HP Compressor

Heating capacity: 7 liters per hour

Chiling capacity: 8 liters per hour

Tank Capacity: Cold Tank (L)3.6 ℓ , Hot Tank (L)1.6 ℓ

Cooling: Temperature Control: Thermostat , Cooling System: Forced Cooling System

Heating: Temperature Control: Thermostar , Heater Type: Sheath Type / Band Type

Overheat Protector: Auto Bi-metal

Weight: 11kg

Dimensions(mm): 310(W)X320(D)X990(H)



# Water Dispenser Catalogue (Filtration / Direct Pipe In Type)



**Model: GWS-C200F**

**Floor Standing  
(Hot & Cold Water)**

Product Specification:

Volt./ Hz: 220-240V/50-60Hz

Power Consumption:

Cooling System: 100W

Heating System: 450W

Compressor: 1/15HP Daewoo Korea Compressor

Heating capacity: 8 liters per hour

Chiling capacity: 10 liters per hour

Tank Capacity: Cold Tank (L)3.6 ℓ , Hot Tank (L)2 ℓ

Cooling: Temperature Control: Thermostat , Cooling System: Forced Cooling System

Heating: Temperature Control: Thermostar , Heater Type: Sheath Type / Band Type

Overheat Protector: Auto Bi-metal

Weight: 19kg

Dimensions: 300mm(W) X 355mm(D) X 1120mm(H)



# Water Dispenser Catalogue (Filtration / Direct Pipe In Type)



**Model: GWS-780F**

**Floor Standing**

**(Hot, Normal & Cold Water)**

Product Specification:

Product Features: Drain Container Collects water drips into the container

With indication float which rises up when container is full.

Push button control panel , LED-lighting on dispensing place.

Safety lock for hot water .

Heating capacity up to 10 liters per hour.

Chilling capacity: 12L / hour, chilled water under 10 degree C.

Capacity : Hot 2.0L , Cold 3.5L , Normal 1.5L

Consumed power : Hot 600W / Cold 210W

Dimension : 260mm (width) x 445mm (depth) x 1100mm (height)



# Water Dispenser Catalogue (Filtration / Direct Pipe In Type)



**Model: GWS-C520F**

**Floor Standing (Hot & Cold Water)**

**Touch Free System**

Product Specification:

Product Features: Double secure prevents from overheat or dry-heat.  
(by sensor and thermostat).

Automatic control for purified water refill.

Each hot and chilled water has its own individual tank..

Hot water with safety device.

Touch Free System

How it works: Hover your glass or bottle in front of the infrared sensor panel and watch it dispense all on its own. No pushing or pressing required.

Heating capacity: 5L / hour.

Hot water temperature around ( 82C~ 90C).

Capacity of each tank: Cold tank : 8 Liters / Hot tank: 1.5 Liters

Weight: F/S: 22 KG

Dimension:F/S :335mm (Width) x 360mm (Depth) x 1015mm (Height)





# Water Dispenser Catalogue (Filtration / Direct Pipe In Type)



**Model: GWS-2100**

**Floor Standing  
(Hot & Cold Water)**

Product Specification:

Volt./ Hz: 220-240V/50-60Hz

Power Consumption:

Cooling System: 100W

Heating System: 450W

Compressor: 1/15HP Daewoo Korea Compressor

Heating capacity: 20 liters per hour

Chiling capacity: 25 liters per hour

Tank Capacity: Cold Tank (L)7.2 ℓ , Hot Tank (L)5 ℓ

Cooling: Temperature Control: Thermostat , Cooling System: Forced Cooling System

Heating: Temperature Control: Thermostar , Heater Type: Sheath Type / Band Type

Overheat Protector: Auto Bi-metal

Weight: 25kg

Dimensions(mm): 340(W)X375(D)X1200(H)



# Water Dispenser Catalogue (Filtration / Direct Pipe In Type)



**Model: GWS-PTS3000**

**Floor Standing (Hot, Normal & Cold Water)**

Product Specification:

Product Features : Double secure prevents from overheat or dry-heat.  
(by sensor and thermostat).

Double secure against water overflow. (by floating valve).

Automatic control for purified water refill.

Each hot and chilled water has its own individual tank.

One Touch Sensor Screen

Hot water with safety device.

One output for three temperature water

Heating capacity: 20L / hour.

Hot water temperature can be assigned (at 82C, 85C, or 90C).

Chilling capacity: 25L / hour, chilled water under 10 degree C.

Chilling system by compressor with 1/15HP LG Korea Compressor

Capacity of each tank: Cold tank : 6 Liters / Hot tank: 2.2 Liters

Weight: 22 KG

Dimension: 300mm (width) x 400mm (depth) x 1110mm (height)



# Water Dispenser Catalogue (Bottles Type)



**Model: GWS-C118N**

**Floor Standing (Top Load)  
(Hot, Normal & Cold Water)**

Product Specification:

Product Features : Double secure prevents from overheat or dry-heat.  
(by sensor and thermostat).

Double secure against water overflow.

Each hot, ambient and chilled water has its own individual tank.

Water Tap : Three temperature water output

Heating capacity: 12L / hour.

Hot water temperature around ( 82C~ 90C).

Hot water tap with safety device

Chilling capacity: 9L / hour, chilled water under 10 degree C.

Chilling system by compressor with R-134a refrigerant.

Capacity of each tank: Cold tank : 3.0 Liters / Hot tank: 1.4 Liters

Dimension : 340mm (width) x 330mm (depth) x 980mm (height)

Weight : 14kg



# Water Dispenser Catalogue (Bottles Type)



**Model: GWS-BY605**

**Floor Standing (Bottom Load)  
(Hot, Normal & Cold Water)**

Product Specification:

Tank Capacity: (Cold) 2L/h / (Hot) 5L/h

Power Consumption: (Cold)85W / (Hot)500W

Voltage: 220V-240V / 50Hz/60Hz

Size(W\*D\*H): 355mm\*390mm\*1115mm

Weight: 16kg



Hot,  
Ambient &  
warm water



Hot water  
safety lock



Bottom  
Load  
Design